




Product Size



Specification

Model No.:	RS-FT54W316X-A(88134) / RS-FT72W316X-A(88134)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D222*H48mm (Nozzle hole size: 65mm)
Tempered Glass:	10mm thickness
LED chip:	CREE / EDISON
LED Q'ty:	18pcs 3W LED / 18pcs 3in1 LED / 18pcs 4in1 LED / 24pcs 3W LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 20° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System / Nozzle fixed
Net Weight:	6.0kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88134.243.01	2700-3000K	24*3	V+/V-	AC/DC24	3000	72	3360
88134.243.02	4000-4500K	24*3	V+/V-	AC/DC24	3000	72	3352
88134.243.03	5000-5500K	24*3	V+/V-	AC/DC24	3000	72	3720
88134.243.04	6000-6500K	24*3	V+/V-	AC/DC24	3000	72	3720
88134.243.05	Red	24*3	V+/V-	AC/DC24	2000	48	840
88134.243.06	Green	24*3	V+/V-	AC/DC24	3000	72	2160
88134.243.07	Blue	24*3	V+/V-	AC/DC24	3000	72	960
88134.243.08	Yellow	24*3	V+/V-	AC/DC24	3000	72	2280
88134.183.09	RGB-DMX512 (3 channel)	18*3	V+ /V- /D+/D- /GND	DC24	R: 500 B: 750 G: 750	R: 12 B: 18 G: 18	R: 210 B: 240 G: 540
88134.183.10	Auto changing color	18*3	V+ /V-	AC24	R: 500 B: 750 G: 750	R: 12 B: 18 G: 18	R: 210 B: 240 G: 540
88134.183.12	RGBV+ (build-in CC driver)	18*3	R/G/B/V+	DC24	R: 500 B: 750 G: 750	R: 12 B: 18 G: 18	R: 210 B: 240 G: 540
88134.243.13	RGBW-DMX512 (4 channel)	24*3	V+ /V- /D+/D- /GND	DC24	R: 500 B: 750 G: 750 W: 750	R: 12 B: 18 G: 18 W: 18	R: 210 B: 240 G: 540 W: 840
88134.183.14	RGB-DMX512 (3 channel)	18*3in1	V+ /V- /D+/D- /GND	DC24	R: 750 B: 750 G: 750	R: 18 B: 18 G: 18	R: 450 B: 540 G: 1080
88134.184.15	RGBW-DMX512 (4 channel)	18*4in1	V+ /V- /D+/D- /GND	DC24	R: 750 B: 750 G: 750 W: 750	R: 18 B: 18 G: 18 W: 18	R: 450 B: 540 G: 1080 W: 1620

